

THE GATOR CX.

A golf cart, it's not.

POPULAR OPTIONS: Cargo box power lift • Front blade • Sun canopy • Front and rear hitch • Deluxe light kit

Don't be fooled by the Gator CX's convenient size, and labor-saving extras. It's capable of doing things golf carts can only imagine. It can lug 400 pounds of brick or gravel. And pull the same heavy-duty cart as other Gators. (You won't find a rear receiver hitch option on a golf cart, now will you?) So take one home. You'll find it can handle more than the front walk.

WEATHERPROOF 12-VOLT DC OUTLET

WET DISC BRAKES

GLOVE BOX

FRONT AND REAR SUSPENSION

DIFFERENTIAL LOCK

Tough, rustproof polyethylene cargo box.

Compact size for tight spaces

Robotically welded tubular steel frame is electrostatically coated and powder painted for maximum rust resistance.

Choose Cayman lawn or street tires, or knobby tires (meant for rougher terrain)



SPECIFICATIONS

Gator CX

Engine and Electrical

Type	9.5 hp* (7.1 kW) Air-cooled overhead-valve 1-cylinder, 4-cycle gas
Displacement	286 cc (17.45 cu. in.)
RPM Idle/fast (no load)	1150 3850
Maximum torque	14.5 lb.-ft @ 2500 rpm

Transmission

Type	Continuous variable trans. (CVT)
Speed, mph	0-15 (0-24 km/h) forward, 0-10 (0-16 km/h) reverse
Differential Lock	Standard, Hand-operated
Transaxle	Fully enclosed, oil bath
Gear Selection	Forward, neutral, reverse

Suspension and Steering

Front	Independent, single A-arm suspension
Total travel	3.25 in. (82 mm)
Rear	Triple-rate spring-over-shock
Total travel	3.5 in. (89 mm)
Steering	Rack and pinion
Turning radius	9.875 ft. (3.0 m)

Brakes

Park brake	Wet disk in transaxle
	Wet disk, hand/foot operated

Tires

Front	18x8.5-8, 4 PR Turf, 18x9.5-8 3 PR Knobby
Rear	20x10-8, 2 PR Turf, 20x11-8 3 PR Knobby

Fuel System

Capacity	3.0 U.S. gal. (11.4 L)
----------	------------------------

Cargo Box

Material	High-density cross-linked polyethylene
Electric lift	Optional
Capacity	400 lb. (181 kg)
Depth	7.8 in. (198 mm)
Length	28.9 in. (734 mm)
Volume	5.0 cu.ft. (.14 cu. m)
Width	38.2 in. (970 mm)
Height above ground	25 in. (635 mm)
Tailgate	Hinged at bottom, removable
Weight, lb. (Incl fuel, fluids)	687 lb. (312 kg)

Seating type

	2, Professional high back bucket seats, tilt forward
Seat adjustment	Slide rail system - 14 positions, 1/2-in. increments

Dimensions

Height	44 in. (1118 mm)
Width	Rear: 49.0 in. (1245 mm), Front: 47.2 in. (1199 mm)
Length with/without bumper	98.2 in. (2494 mm)/95.7 in. (2431 mm)

Ground clearance, under foot platform	4.8 in. (122 mm)
under transaxle	7.0 in. (178 mm)
Wheelbase	65.5 in. (1663 mm)

Payload/Towing capacity

	800 lb. (363 kg)/600 lb. (272 kg)
--	-----------------------------------

* Engine hp is provided by engine mfr. for comparison purposes only. Actual operating hp will be less.