

Manufacturer	John Deere
Model	317 G Tier 4 Final
DESCRIPTION	
Lift Geometry	Vertical
DRIVELINE	
Engine Manufacturer	Yanmar
Engine Model	4TNV86CHT
Emission Rating	Tier 4
Aspiration	Turbo
Displacement, ltr (Inches ³)	2.1 (128)
Rated Speed, rpm	2600
Engine Output - Net, kW (hp)	45.6 (61)
Engine Output - Gross, kW (hp)	48.5 (65)
Torque, Nm (lbf / ft)	207 (153)
Track Shoe Width, mm (inches)	320 (12.6)
DIMENSIONS	
Length - No Bucket, mm (inches)	2630 (103)
Length - With Bucket, mm (inches)	3240 (127.6)
Width - No Bucket, mm (inches)	1650 (65.1)
Height - Top Of Cab, mm (inches)	1990 (78.5)
Ground Clearance, mm (inches)	210 (8.3)
Rear Departure Angle, °	32.3
Track Gauge, mm (inches)	1330 (52.5)
Height to Hinge Pin, mm (inches)	3070 (121)
Dump Angle, °	42
Dump Height - Maximum, mm (inches)	2430 (95.6)
Rollback - Ground Level, °	30
CAPACITIES	
Fuel Tank, ltr (gallons (US))	71 (19)
PERFORMANCE	
Rated Operating Capacity, kg (lbs)	965 (2125)
Tipping Load, kg (lbs)	2756 (6070)
Ground Bearing Pressure, kPa (PSI)	38 (5.5)
Speed - Maximum, kph (mph)	11.3 (7)
Breakout - Lift, kN (lbf)	22.2 (5000)
Breakout - Bucket, kN (lbf)	26.6 (6000)
Hydraulic Power, kW (hp)	23.159 (31)
Pump Flow, lt/min (gallons (US) / min)	59 (16)
System Pressure, bar (PSI)	237.87 (3450)
WEIGHTS	
Operating Weight, kg (lbs)	3721 (8195)

Specifications are based on published information at the time of publication. Specifications are subject to change without notice.

Prices are subject to change without notice. Prices are in dollars and only applicable to products sold in the United States. In all cases, current published price lists and incentive program bulletins will take precedence. All trademarked terms, including John Deere, the leaping deer symbol and the colors green and yellow used herein are the property of Deere & Company, unless otherwise noted.