

2305

The compact tractor that performs at a much larger size.

When it comes to exceeding expectations, the John Deere 2305 is an overachiever in its class. Four-wheel drive, mid- and rear-PTOs and a three-point hitch are all standard. Comforts include adjustable seats, effortless two-pedal hydrostatic transmission, color-coded controls – and 2.5-inch thick rubber engine isolators that tone down engine noise and vibration. So take a look at what a 2305 can do for you. You'll be amazed at how much tractor you get. And if you'd like to go one step further, build your own 2305 Tractor online at www.JohnDeere.com/2000.



- 1 **Standard four-wheel drive** makes loader work that much easier
- 2 **Liquid-cooled diesel engines** run cleanly and quietly.
- 3 **Both mid- and rear PTOs** are standard. You can work with implements like snowblowers, mower decks and tillers.
- 4 **Engine isolated from frame and transmission** for much quieter operation.
- 5 **HST Transmission** with Twin Touch™ foot pedals allows for increased performance.



2305



OTHER OPTIONS

- Canopy
- Cruise control
- Forward work lights
- Front weights
- Hood guard
- Independent hydraulic mower lift
- Mechanical hydraulic diverter
- Rear wheel weights
- Rear work light
- Tire chains
- Umbrella
- Warning light guards

2305 Dimensions





Twin Touch™ transmission pedals make it easy to switch from forward to reverse, and let you rest your heel on the platform the whole time you drive.



Standard, easy-to-use cruise control lets you concentrate on the task at hand.

NO ONE BUILDS OR BACKS TRACTORS BETTER THAN JOHN DEERE.

It's the fine print, but a big story: Every John Deere Compact Tractor comes with a 3-year/2000-hour limited warranty. See your dealer for details.



OTHER OPTIONS

- Canopy
- Forward work lights
- Front weights
- Hood guard
- Independent hydraulic mower lift
- Mechanical hydraulic diverter
- Power beyond hydraulics
- Rear wheel weights
- Rear work light
- Umbrella
- Warning light guards

- Optional Independent Lift Kit** uses tractor hydraulics to raise and lower deck, independent of the 3-point hitch position.
- Folding ROPS** are standard and comply with ASAE and OSHA standards.
- Hydrostatic power steering** for smooth and steady maneuvering.
- On Ramp Drive Over Deck** allows for easy attaching of mower deck
- 200 CX loader** can attach and detach in under 3 minutes – with no tools.
- Convenient loader joystick** is positioned close at hand and clear of your knee.

5



Wheelbase - 63 in. (1600 mm) (2320)
65.2 in. (1655 mm) (2520, 2720)

Length - 109.2 in. (2774 mm) (2320)
108.9 in. (2766 mm) (2520, 2720)

Hood height - 53.3 in. (1355 mm) (2320)
47.2 in. (1200 mm) (2520, 2720)



Min. width - 37.1 in. (941 mm) (2320)
39.2 in (995 mm) (2520, 2720)

Width - 51 in. (1295 mm) (2320)
52.6 in. (1336 mm) (2520, 2720)

Folded ROPS height - 67.9 in. (1725 mm) (2320)
68.9 in. (1750 mm) (2520, 2720)
Height - 89 in. (2261 mm) (2320)
89.7 in. (2279 mm) (2520, 2720)