

Gator™ Traditional UTILITY Vehicles

Add Versatility With:

- Adjustable Driver's Seat
- Back-Up Alarm
- Ball Hitch
- Battery Maintainer
- Bedliner
- Brake/Tail Light Kit
- Cargo Box Mat
- Deluxe Light Kit (Includes Turn Signals, 4-Way Flashers, Brake and Tail Lights, and Side Mirrors)
- Mirrors
- Fender Guards
- Floormat
- 54- and 72-Inch Front Blade
- 72-Inch V-Blade
- 72-Inch HD Front Blade
- Front Brush Guard
- Front Bumper (Standard on TH and HPX)
- Gauge Package (TS, TX and TH only)
- Grab Light
- Glass Door Cab
- Heavy-Duty Front Suspension
- High-Capacity Alternator
- Hitch Drawbar Kit
- Horn
- Cargo Box Power Lift Kit
- Rear Hitch
- Rear Receiver Hitch
- Rough Terrain Kit
- "Truck-Style" Toolbox
- 21, 17, 10 AT Utility Cart
- 3,000-Pound Winch
- Winch Accessories Kit
- Windscreen
- Windshield Wiper
- Front/Rear Work Lights



Gator CX



Gator TS



Gator TH



Gator TX



Gator HPX 4x4

FEATURES

- 2-WD and 4-WD models feature gas, diesel and electric motors.
- Models range from 15 mph to a top speed of 25 mph (24 - 40 km/h).
- Standard hand-operated traction assist locks rear drive wheels together to power through areas requiring additional traction.
- The available glass cab is certified to SAE (Society of Automotive Engineers) and equivalent European standards for rollover protection.
- Both steel and composite boxes available. The cargo box sets for low easy loading and unloading.
- High flotation tires on the TS and TH 6x4 minimize ground compaction to protect turf and prevent ruts in soft ground.
- The available diesel engine is an 854 cc liquid cooled 3 cylinder engine that provides incredible performance while meeting all new CARB requirements.
- A low center of gravity provides best-in-class stability for assurance at higher speed or on inclines.
- Standard features include cupholders, 12V DC outlet, glove box and fuel gauge.

EIGHT MODELS AVAILABLE

- **Gator CX**
286 cc (9.5 hp*) engine
800-lb. payload capacity[†]
Standard differential lock
Rear wet disc brakes
Standard 12V DC outlet
Full vehicle suspension
independent front, semi-independent rear
- **Gator TS**
351 cc (11.1 hp*) gas engine
Mid-back bucket seats
900-lb. payload[†]/towing capacity
Rear wet-disc brakes
10.1 cu. ft. (.29 m³) cargo box - steel
- **Gator TX**
675 cc (19 hp*) gas engine
High-back bucket seats
1,000-lb. payload[†]/towing capacity
Four-wheel hydraulic disc brakes
Full vehicle suspension
16.4 cu. ft. (.46 m³) cargo box
- **Gator TH 6x4**
675 cc (19 hp*) gas engine
High-back bucket seats
1,400-lb. payload[†]/towing capacity
Rear wet-disc brakes
16.4 cu. ft. (.46 m³) cargo box

- **Gator TH 6x4 Diesel**
854 cc (20.8 hp*) diesel engine Tier 2 compliant
High-back bucket seats
1,600-lb. payload[†]/towing capacity
Rear wet-disc brakes
16.4 cu. ft. (.46 m³) cargo box
Standard front bump *

- **Gator TE (Electric model)**
6.0 hp* (4.6 kw) DC motor (30 min. S2 rating)
48 volt system
High-back bucket seats
900-lb. payload[†]/600-lb. towing capacity
16.4 cu. ft. (.46 m³) cargo box

- **Gator HPX 4x4**
617 cc (20 hp*) gas engine
1,400 lb. payload[†]/1,300 lb. towing
4-wheel disc brakes
4-wheel suspension
25 mph

- **Gator HPX Diesel 4x4**
854 cc (20.8 hp*) diesel engine
1,400 lb. payload[†]/1,300 lb. towing
4-wheel disc brakes
4-wheel suspension
25 mph

[†]Includes 200-lb. (91 kg) operator and 200-lb. (91 kg) passenger and maximum box capacity.

* Engine horsepower is provided by engine manufacturer for comparison purposes only. Actual operating horsepower will be less.

SPECIFICATIONS

Gator CX

Engine and Electrical:

Type	.286 cc, 1-cylinder, 4-cycle OHV gas
Horsepower*	9.5 (7.1 kW)
Maximum Torque	14.5 lb.-ft. @ 2,500 rpm
Ignition Type	Magneto solid state
Lubrication	Full pressure
Oil Filter	Optional
RPM, Idle (No Load)	1,125
RPM, Fast (No Load)	3,850
Cooling System	Air
Air Cleaner	Single-element paper, replaceable
Muffler	Optional spark arrestor
Battery	U1, 160 CCA
Alternator	13 amp, regulated
Headlights	Two at 25 watts, 12-volt DC
DC Outlet	Standard

Fuel System:

Capacity	3.0 gal. (11.4 L)
Consumption (Half Load at Avg. Speed)	0.4 gal./hr. (1.5 L/hr.)
Fuel Pump Type	Vacuum pulse

Transmission:

Type	Continuously variable transmission (CVT) w/traction assist
Traction Assist	Standard, hand-operated
Ground Speed	0-15 mph (0-24 km/h)
Transaxle	Fully enclosed; oil bath
Gear Selection	Forward, neutral, reverse
Brakes	Wet disc in transaxle
Park Brake	Wet disc, hand/foot-operated

Suspension and Steering:

Suspension, Front	Independent, dual rate, spring-over-shock, single A-arm w/adj. preload
Suspension Travel (Total)	3.25 in. (82 mm)
Suspension, Rear	Three-point, semi-independent, triple rate, spring-over-shock w/adj. preload
Steering	Rack and pinion

Dimensions:

Length (w/Bumper)	98.2 in. (2495 mm)
Width	49.0 in. (1245 mm)
Height (Overall)	44 in. (1118 mm)
Wheelbase	65.5 in. (1663 mm)
Weight (Including Fuel/Fluids)	687 lb. (312 kg)
Ground Clearance:	
Under Transaxle	4.8 in. (121 mm)
Under Foot Platform	7.0 in. (178 mm)
Turn Clearance Circle	19 ft. 9 in. (6.0 m)
Towing Capacity (On Level Terrain)	600 lb. (272 kg)
Payload Capacity	800 lb. (363 kg)

Seats:

Seat Type	Professional high-back bucket seat, tilt forward
-----------	--

Cargo Box:

Dimensions	28.9 in. L × 38.2 in. W × 7.8 in. D (735 mm L × 970 mm W × 198 mm D)
Volume	5 cu. ft. (0.14 cu. m)
Weight Capacity	400 lb. (182 kg)
Features	Molded-in divider slots, tie-down attaching points, lift handle

Tires:

Available Tread Types	Turf or knobby
Other Standard Features	Dual cupholders, glove box, hourmeter, fuel sight gauge, 12 volt DC outlet

*Engine horsepower is provided by engine manufacturer for comparison purposes. Actual operating horsepower may be less.

SPECIFICATIONS

	Gator HPX 4x4	Gator HPX 4x4 Diesel
Engine and Electrical:		
Type	2-cylinder, 4-cycle OHV gas	3-cylinder, 4-cycle OHV diesel
Horsepower*	20 (15 kW)	20.8 (15.5 kW)
Displacement	617 cc	854 cc
Maximum Torque	32 ft.-lb. (4.4 kg-m @ 2500 rpm)	33 ft.-lb. (4.5 kg-m @ 3350 rpm)
Ignition Type	Solid state 12V	Solid state 12V
Lubrication	Full pressure	Full pressure
Cooling System	Liquid	Liquid
Air Cleaner	Dry replaceable single-element w/remote intake	Dry replaceable duel element w/remote intake
Battery	340 CCA	480 CCA
Alternator	21 amp @ 3200 rpm—regulated, 3 phase	40 amp @ 3200 rpm—regulated
Headlights	Two 37.5 watt halogen	Two 37.5 watt halogen
Fuel Capacity 5.3 U.S. gal. (20.0 L)		
Transmission:		
Type	Continuously variable transmission (CVT)	Continuously variable transmission (CVT)
4WD	Operator selectable On-Demand "True" 4WD	Operator selectable On-Demand "True" 4WD
Traction Assist	Standard rear differential lock	Standard rear differential lock
Ground Speed:		
High Range	0-25 mph (0-40 km/h)	0-25 mph (0-40 km/h)
Low Range	0-12 mph (0-19 km/h)	0-12 mph (0-19 km/h)
Transaxle	Two-speed, oil bath	Two-speed, oil bath
Gear Selection	Forward (high-low), neutral, reverse	Forward (high-low), neutral, reverse
Brakes	Front/rear hydraulic disk	Front/rear hydraulic disk
Park Brake	Rear hydro-mechanical disk	Rear mechanical disk, hand operated
Suspension and Steering:		
Suspension, Front	Independent w/MacPherson strut	Independent w/MacPherson strut
Suspension, Rear	Coil over shock	Coil over shock
Ground Clearance:		
Under Transaxle	6 in. (153 mm)	6 in. (153 mm)
Under Foot Platform	12 in. (305 mm)	12 in. (305 mm)
Steering	Rack and pinion	Rack and pinion
Occupant Protection System SAE and OSHA ROPS certified steel tubular structure w/3-pt. belts and multiple handholds		
Dimensions:		
Length (w/Bumper)	113.0 in. (2870 mm)	113.0 in. (2870 mm)
Width	59.3 in. (1506 mm)	59.3 in. (1506 mm)
Front-Tread Centers	49.5 in. (1257.3 mm)	49.5 in. (1257.3 mm)
Rear-Tread Centers	48 in. (1219.3 mm)	48 in. (1219.3 mm)
Height (Overall w/OPS)	73.5 in. (1867 mm)	73.5 in. (1867 mm)
Wheelbase	75.2 in. (1910 mm)	75.2 in. (1910 mm)
Weight (Including Fuel/Fluids)	1296 lb. (589 kg)	1473 lb. (668 kg)
Turn Clearance Circle	22 ft. (6.7 m)	11 ft. (3.35 m)
Seating Capacity, Type	2, Professional high-back	2, Professional high-back
Towing/Payload Capacity ¹	1,300 lb. (590 kg)/ 1,400 lb. (635 kg)	1,300 lb. (590 kg)/ 1,400 lb. (635 kg)
Cargo Box Heavy-duty steel		
Load Height	31 in.	31 in.
Dimensions	43.9 in. L x 49 in. W x 9 in. D (1116 mm L x 1244 mm W x 229 mm D)	43.9 in. L x 49 in. W x 9 in. D (1116 mm L x 1244 mm W x 229 mm D)
Volume	11.2 cu. ft.	11.2 cu. ft.
Max. Box Weight	1,000 lb. (454 kg)	1,000 lb. (454 kg)
Front Tires All types = 24x9.50-10 / 4-ply		
Rear Tires All Purpose HPAP = 24x10.5-10 (4-ply)		
	Aggressive Tread HPAT = 24x12-10 (4-ply)	Aggressive Tread HPAT = 24x12-10 (4-ply)
	Turf/hard-surface = 24x12-10 (4-ply)	Turf/hard-surface = 24x12-10 (4-ply)
Standard Tread Type	All Purpose HPAP	All Purpose HPAP

*Engine horsepower is provided by engine manufacturer for comparison purposes. Actual operating horsepower may be less.

¹Includes 200-lb. (91 kg) operator and 200-lb. (91 kg) passenger and maximum box capacity.

SPECIFICATIONS

	Gator TS	Gator TX	Gator TE
Engine and Electrical:			
Type	351 cc, 1-cylinder, 4-cycle OHV gas	675 cc, 2-cylinder, 4-cycle OHV gas	-See Page 262 for Specifications
Horsepower*	11.1 (8.3 kW)	19 hp (14.2 kW)	
Maximum Torque	17.4 lbf-ft @ 2,500 rpm	37 lbf-ft @ 2,400 rpm	
Ignition Type	Magneto, solid state 12V	Magneto, solid state 12V	
Lubrication	Full pressure	Full pressure	
Oil Filter	Replaceable (standard)	Screw-on	
RPM, Idle/Fast (No Load)	1125 +/- 75 / 3850 +/- 75	1125 +/- 75 / 3750 +/- 75	
Cooling System	Air	Air	
Air Cleaner	Dry replaceable single-element	Dry replaceable single-element	
Muffler	Spark-arresting	Spark-arresting	
Battery	38 amp/hr.; 340 CCA	38 amp/hr.; 340 CCA	
Alternator	13-amp @ 3,600 rpm, regulated	16.6 amp @ 3,700 rpm, regulated	
Headlights	Two 37.5 watt halogen	Two 37.5 watt halogen	
Fuel Capacity	5.0 U.S. gal. (18.9 L)	5.0 U.S. gal. (18.9 L)	
Transmission:			
Type	Continuously variable transmission (CVT)	Continuously variable transmission (CVT)	
Traction Assist	Standard, hand-operated	Standard, hand-operated	
Drive Chain	N/A	N/A	
Ground Speed, Forward	0-20 mph (0-32 km/h)	0-20 mph (0-32 km/h)	
Transaxle	Fully enclosed, oil bath	Fully enclosed, oil bath	
Gear Selection	Forward, neutral, reverse	Forward, neutral, reverse	
Brakes	Wet disc in transaxle	Front and rear hydraulic disk	
Parking Brake	Wet disk, hand operated	Rear mechanical disk, hand operated	
Suspension and Steering:			
Suspension, Front	Independent, spring over shock, single A-arm	Independent, spring over shock, single A-arm	
Suspension, Rear	N/A	Semi-independent, adjustable coil over shuk	
Steering	Rack-and-pinion	Rack-and-pinion	
Ground Pressure (Max.):			
With 200 lb. Operator Only	5.6 psi	6.2 psi	
Fully Loaded Vehicle	7.5 psi	11.6 psi	
Dimensions:			
Length/Width/Height (w/Bumper)	104 in.×60.0 in.×43.6 in. (2642 mm×1525 mm×1108 mm)	112.1 in.×60.0 in.×43.6 in. (2746 mm×1525 mm×1108 mm)	
Front-Tread Centers	50 in. (1270 mm)	50 in. (1270 mm)	
Rear-Tread Centers	48 in. (1219 mm)	48 in. (1219 mm)	
Wheelbase	69.7 in. (1770 mm)	72.5 in. (1841 mm)	
Weight (Including Fuel/Fluids)	915 lb. (415 kg)	1,032 lb. (468 kg)	
Turn Clearance Circle	22.5 ft. (6.9 m)	22.5 ft. (6.9 m)	
Seating Capacity/Type	2, Standard medium-back	2, Professional high-back	
Towing/Payload Capacity [†]	900 lb. (408 kg)	1,000 lb. (454 kg)	
Ground Clearance:			
Under Transaxle	6.0 in. (152.4 mm)	5.7 in. (145 mm)	
Under Foot Platform	9.8 in. (250 mm)	10.6 in. (270 mm)	
Cargo Box			
	Steel	Steel/composite	
Volume	10.1 cu. ft. (.29 m ³)	16.4 cu. ft. (.46 m ³)	
Max. Weight	500 lb. (227 kg)	600 lb. (272 kg)	
Length/Width/Depth	39.5 in.×49 in.×10 in. (1003 mm×1245 mm×229 mm)	45 in.×52 in.×12 in. (1143 mm×1320 mm×304 mm)	
Load Height	25 in. (635 mm)	29 in. (737 mm)	
Tailgate	Removable; hinged at bottom	Removable; hinged. side panels are removable	
Tires:			
Available Tread Types	Knobby, turf, all-terrain, run-flat	Turf, all-terrain, extreme terrain, run-flat	

*Engine horsepower is provided by engine manufacturer for comparison purposes. Actual operating horsepower may be less.

[†]Includes 200-lb. (91 kg) operator and 200-lb. (91 kg) passenger and maximum box capacity.

SPECIFICATIONS

	Gator TH 6×4	Gator TH Diesel 6×4
Engine and Electrical:		
Type	675 cc, 2-cylinders, 4-cycle OHV gas	854 cc 3-cylinders, 4-cycle OHV diesel
Horsepower*	19.0 (14.2 kW)	20.8 (15.5 kW)
Maximum Torque	37.0 lb.-ft. @ 2400 rpm	34.6 lb.-ft. @ 2400 rpm
Ignition Type	Magneto, solid state 12V	IDI diesel
Lubrication	Full pressure	Full pressure
Oil Filter	Screw-on filter	Replaceable (standard)
RPM, Idle/Fast (No Load)	1125 +/- 75 / 3700 +/- 75	1050 +/- 25 / 3650 +/- 25
Cooling System	Air	Liquid
Air Cleaner	Dry replaceable single-element	Dry replaceable, dual-element
Muffler	Spark-arresting	Spark arresting (optional)
Battery	38 amp/hr.; 340 CCA	38 amp/hr.; 340 CCA
Alternator	16.6 amp @ 3600, regulated	40 amp regulated
Headlights	Two 37.5 watt halogen	Two 37.5 watt halogen
Fuel Capacity 5.0 U.S. gal. (18.9 L)		
Transmission:		
Type	Continuously variable transmission (CVT)	Continuously variable transmission (CVT)
Traction Assist	Standard, hand-operated	Standard, hand-operated
Drive Chain	#60 industrial	#60 industrial
Ground Speed, Forward	0-20 mph (0-32 km/h)	0-20 mph (0-32 km/h)
Transaxle	Fully enclosed, oil bath	Fully enclosed, oil bath
Gear Selection	Forward, neutral, reverse	Forward, neutral, reverse
Brakes	Wet disk in transaxle	Wet disk in transaxle
Parking Brake	Wet disk, hand operated	Wet disk, hand operated
Suspension and Steering:		
Suspension, Front	Independent, spring over shock, single A-arm	Independent, spring over shock, single A-arm
Suspension, Rear	N/A	N/A
Steering	Rack-and-pinion	Rack-and-pinion
Ground Pressure (Max.):		
With 200 lb. Operator Only	6.9 psi	6.9 psi
Fully Loaded Vehicle	7.1 psi	7.3 psi
Dimensions:		
Length/Width/Height (w/Bumper)	108.4 in.×60.0 in.×43.6 in. (2753 mm×1525 mm×1108 mm)	108.4 in.×60.0 in.×43.6 in. (2753 mm×1525 mm×1108 mm)
Front-Tread Centers	50 in. (1270 mm)	50 in. (1270 mm)
Rear-Tread Centers	48 in. (1219 mm)	48 in. (1219 mm)
Wheelbase	79.0 in. (2006 mm)	79.0 in. (2006 mm)
Weight (Including Fuel/Fluids)	1,087 lb. (493 kg)	1,310 lb. (594 kg)
Turn Clearance Circle	24.5 ft. (7.5 m)	24.6 ft. (7.5 m)
Seating Capacity/Type	2, Professional high-back	2, Professional high-back
Towing/Payload Capacity†	1,400 lb. (635 kg)	1,400 lb. (635 kg) towing capacity / 1,600 lb. (725 kg) payload capacity
Ground Clearance:		
Under Transaxle	6.7 in. (170 mm)	6.5 in. (165 mm)
Under Foot Platform	9.8 in. (250 mm)	8.5 in. (215 mm)
Cargo Box Steel/composite		
Volume	16.4 cu. ft. (0.46 m³)	16.4 cu. ft. (0.46 m³)
Max. Weight	600 lb. (272 kg)	600 lb. (272 kg)
Length/Width/Depth	45 in.×52 in.×12 in. (1143 mm×1320 mm×304 mm)	45 in.×52 in.×12 in. (1143 mm×1320 mm×304 mm)
Load Height	29 in. (737 mm)	29 in. (737 mm)
Tailgate	Removable; hinged, side panels are removable	Removable; hinged, side panels are removable
Tires:		
Available Tread Types	Turf, knobby, all-terrain, run-flat	Turf, knobby, all-terrain, run-flat

*Engine horsepower is provided by engine manufacturer for comparison purposes. Actual operating horsepower may be less.

†Includes 200-lb. (91 kg) operator and 200-lb. (91 kg) passenger and maximum box capacity.