



XUV 825i

- Heavy Duty POWERtach Blade, 72"
- POWERtach Markers
- POWERtach Poly Wear Bar
- POWERtach Rubber Squeegee
- POWERtach Skid Shoes
- POWERtach Deflector Shield
- Standard Straight Blade, 72"
- Standard V-Shape Blade, 72"
- Deluxe Glass Cab
- Cab Heater
- Side Mirrors, Deluxe Cab
- Windshield Washer Fluid Kit, Deluxe Cab
- Beacon Light Kit - Deluxe Cab
- OPS Side Mirror - Left
- OPS Side Mirror - Right
- OPS Full Poly Windshield
- Glass Windshield w/Wiper - OPS
- Front Light Kit- Deluxe Cab
- Rear Light Kit - Deluxe Cab
- OPS Half Poly Windshield
- OPS Poly Cab - Black
- OPS Poly Roof- Black
- OPS Poly Roof - Camo
- OPS Rear Screen
- OPS Soft Roof - Black
- OPS Soft Roof - Camo
- Cargo Box Divider
- Cargo Box FenderGuard
- Cargo Box Bed Mat
- Cargo Box Power Lift
- Cargo Box Side Extensions
- Deluxe Cargo Box Cover - Black
- Deluxe Cargo Box Cover - Camo
- Front Hood Rack
- Heavy Duty Brush Guard
- Heavy Duty Front Fender Guard
- Heavy Duty Rear Bumper
- Rear CV Guards
- Front CV Guards
- Gear Organizer - Black
- OPS Overhead Organizer - Black
- OPS Overhead Organizer - Camo
- Saw Press
- Side Storage Box
- Side Tool Rack
- Spray-on Bedliner
- Tailgate Extender
- Tool Box
- 10 AT Utility Cart
- 17AT Utility Cart
- Fox® HP Racing Shox
- High Performance Slip-On Exhaust
- OPS Overhead Stereo
- Seat-Belt Comfort Strap (2)
- Frontier Food Plot Seeder
- Gear Organizer- Camo
- Vehicle Cover, Cab/ROPS-Camo
- Backup Alarm
- Beacon Light Kit -OPS
- Brake/Tail Light Kit
- Deluxe Signal Light Kit
- Horn Kit
- Mid-Range Light Kit
- Long-Range Light Kit
- Tail light protectors
- Warn® Flood Light Kit
- Floormats
- Warn® Winch 3,000lb.
- 45 Gallon High Performance Sprayer
- 45 Gallon Sprayer, Tow-Behind
- 90 Gallon High Performance Sprayer
- Gator Pal Pressure Washer

FEATURES

- Standard Occupant Protective Structure (OPS) delivers improved styling and protection for the operator with rugged and sporty "off-road" looks. Structure is SAE and OSHA ROPS Certified.
- Best-in-class stability for assurance at higher speed or on inclines.
- On-demand "True" 4WD system with an auto-locking front differential and dash-mounted electronic switch to provide exceptional traction in challenging conditions.
- Front and rear hydraulic service brakes with mechanical driveline disk park brake provides an automotive-style brake system with a dual-circuit for the greatest reliability and a smoother-feeling engagement.
- Independent double wishbone rear suspension on the XUV models provides superior ride over any terrain. 8 in. front and 9 in. rear wheel travel.
- 11 inches of ground clearance on the XUV models will clear the toughest terrain without getting hung up.
- XUV gas models have a 50 hp*, 812 cc liquid cooled 12 valve, DOHC, EFI in-line 3 cylinder engine or a 23 hp*, 617 cc liquid cooled twin cylinder engine with EFI.
- The diesel engine in the XUV 855D is a 25 hp*, 854 cc liquid cooled 3 cylinder engine that provides incredible performance while meeting all new CARB requirements.
- 44 mph top speed on XUV 825i, 32 mph top speed on XUV 855D and 30 mph top speed on XUV 625i.
- 1,000-pound cargo box capacity and 1,400-pound payload/1,500-pound towing capacity.
- Two-speed transmission to allow for superior low-speed pulling & towing ability.
- Hydroformed frame for unmatched strength and durability.
- Engineered plastic (JDLOY) is paintable and provides improved scratch and marring resistance/recoverability.
- Bumper and 2 inch front and rear receivers standard.
- Attractive styling with integrated features, such as cupholders, 12V outlet, glove box, storage compartment and fuel gauge.

THREE MODELS AVAILABLE

- **XUV 825i**
50 hp*, 812 cc EFI gas engine
1,400 lb. payload/1,500 lb. towing[†]
4-wheel disc brakes
Independent rear suspension
11-in. ground clearance
44 mph top speed
2-in. front and rear receiver hitch (standard)
16.4 cu. ft. deluxe cargo box
Digital instrument cluster
Brake, tail and reverse lights
- **XUV 625i**
23 hp*, 617 cc EFI gas engine
1,400 lb. payload/1,500 lb. towing[†]
4-wheel disc brakes
Independent rear suspension
11-in. ground clearance
30 mph top speed
2-in. front and rear receiver hitch (standard)
16.4 cu. ft. deluxe cargo box
- **XUV 855D**
25 hp*, 854 cc diesel engine
1,400 lb. payload/1,500 lb. towing[†]
4-wheel disc brakes
Independent rear suspension
11-in. ground clearance
32 mph top speed
2-in. front and rear receiver hitch (standard)
16.4 cu. ft. deluxe cargo box

* Engine horsepower is provided by engine manufacturer for comparison purposes only. Actual operating horsepower will be less.

[†] Includes 200-lb. (91 kg) operator and 200-lb. (91 kg) passenger and maximum box capacity

SPECIFICATIONS

	Gator XUV 825i	Gator XUV 625i	Gator XUV 855D
Engine and Electrical:			
Type.....	4-cycle gas, Electronic Fuel Injection (EFI)	4-cycle gas, Electronic Fuel Injection (EFI)	4-cycle diesel
Cylinders/Valving	3, DOHC, 4 valves per cyl.	2, OHV	3, OHV
Horsepower*	50 (37.28 kW)	23 (17.2 kW)	25 (18.6 kW)
Displacement.....	812 cc	617 cc	854 cc
Maximum Torque.....	47 ft.-lb. (64 Nm) @3200 rpm	34.6 ft.-lb. (46.9 Nm) @ 2100 rpm	36.9 ft.-lb. (50 Nm) @ 2400 rpm
Cooling System	Liquid	Liquid	Liquid
Battery	340 CCA	340 CCA	480 CCA
Alternator.....	75 amp @ 6000 rpm, regulated, 1012 watts	25.5 amp @ 3200 rpm regulated, 306 watts	40 amp @ 3200 rpm regulated, 540 watts
Lights			
Headlights.....	Two 27 watt halogen	Two 27 watt halogen	Two 27 watt halogen
On-demand true 4WD system			
Front Differential	Auto-locking	Auto-locking	Auto-locking
Rear Differential	Positive locking, mechanically actuated	Positive locking, mechanically actuated	Positive locking, mechanically actuated
Transmission:			
Type.....	(CVT) with full clutch enclosure	(CVT) with full clutch enclosure	(CVT) with full clutch enclosure
Ground Speed mph (km/h)	0-44 mph (0-71 km/h) hi, forward 0-27 mph (0-43 km/h) lo forward 0-30 mph (0-48 km/h) reverse	0-30 mph (0-48 km/h) hi forward 0-17 mph (0-27 km/h) lo forward 0-20 mph (0-32 km/h) reverse	0-32 mph (0-52 km/h) hi forward 0-15 mph (0-24 km/h) lo forward 0-18 mph (0-29 km/h) reverse
Transaxle	Two-speed (hi-lo), oil bath	Two speed (hi-lo) oil bath	Two speed (hi-lo) oil bath
Gear Selection	Forward (hi-lo), neutral, reverse	Forward (hi-lo), neutral, reverse	Forward (hi-lo), neutral, reverse
Front/Rear Brakes	Hydraulic disk with twin piston front calipers	Hydraulic disk with twin piston front calipers	Hydraulic disk with twin piston front calipers
Parking Brake	Driveline, internal wet multi-disc	Driveline, internal wet multi-disc	Driveline, internal wet multi-disc
Bearings	Sealed, double-row ball	Sealed, double-row ball	Sealed, double-row ball
Suspension and Steering:			
Suspension, Front	Fully independent dual control arm with adjustable spring preload	Fully independent dual control arm with adjustable spring preload	Fully independent dual control arm with adjustable spring preload
Front Suspension Travel	8 in. (203 mm)	8 in. (203 mm)	8 in. (203 mm)
Suspension, Rear	Fully independent dual control arm with adjustable spring preload and sway bar	Fully independent dual control arm with adjustable spring preload and sway bar	Fully independent dual control arm with adjustable spring preload and sway bar
Rear Suspension Travel (Total)	9 in. (228.6 mm)	9 in. (228.6 mm)	9 in. (228.6 mm)
Turning Radius.....	15.9 ft. (4.8 m)	15.9 ft. (4.8 m)	15.9 ft. (4.8 m)
Hitches Front and Rear	Standard 2 in. (50.8 mm) receiver	Standard 2 in. (50.8 mm) receiver	Standard 2 in. (50.8 mm) receiver
Occupant Protection System (OPS)			
Tubular Overhead Structure	1.75 in. (44.4 mm) steel tube	1.75 in. (44.4 mm) steel tube	1.75 in. (44.4 mm) steel tube
Seat Belts	3-point seat belts	3-point seat belts	3-point seat belts
Certification.....	SAE J2194 and OSHA ROPS	SAE J2194 and OSHA ROPS	SAE J2194 and OSHA ROPS
Dimensions:			
Length/Width/Height (w/Bumper and OPS) ..	119 in.×62 in.×75 in. (3035 mm×1571 mm×1903 mm)	119 in.×62 in.×75 in. (3035 mm×1571 mm×1903 mm)	119 in.×62 in.×75 in. (3035 mm×1571 mm×1903 mm)
Front-Tread Centers	44.8 in. (1137 mm)	44.8 in. (1137 mm)	44.8 in. (1137 mm)
Rear-Tread Centers	47.9 in. (1216 mm)	47.9 in. (1216 mm)	47.9 in. (1216 mm)
Wheelbase.....	79 in. (2007 mm)	79 in. (2007 mm)	79 in. (2007 mm)
Weight (dry weight)	1,630 lb. (739 kg)	1,630 lb. (739 kg)	1,630 lb. (739 kg)
Towing Capacity*	1,500 lb. (680 kg)	1,500 lb. (680 kg)	1,500 lb. (680 kg)
Payload Capacity*	1,400 lb. (635 kg)	1,400 lb. (635 kg)	1,400 lb. (635 kg)
Ground Clearance:			
Front and Rear.....	11 in. (280 mm)	11 in. (280 mm)	11 in. (280 mm)
Under Foot Platform	12.25 in. (311 mm)	12.25 in. (311 mm)	12.25 in. (311 mm)
Cargo Box			
.....	Hybrid steel/glass-filled poly	Hybrid steel/glass-filled poly	Hybrid steel/glass-filled poly
Volume	16.4 cu. ft. ³ (0.46 m ³)	16.4 cu. ft. ³ (0.46 m ³)	16.4 cu. ft. ³ (0.46 m ³)
Max. Weight	1,000 lb. (454 kg)	1,000 lb. (454 kg)	1,000 lb. (454 kg)
Dimensions.....	45in.×12 in.×52 in. (1143 mm×304.8 mm×1320 mm)	45in.×12 in.×52 in. (1143 mm×304.8 mm×1320 mm)	45in.×12 in.×52 in. (1143 mm×304.8 mm×1320 mm)
Dump	Manual with lift assist shock (factory installed power lift option)	Manual with lift assist shock (factory installed power lift option)	Manual with lift assist shock (factory installed power lift option)
Tailgate	Center truck-style latch	Center truck-style latch	Center truck-style latch
Tires			
Maxxis Big Horn 2.0 Radial: front / rear	27x9xR14 / 27x11xR14	27x9xR14 / 27x11xR14	27x9xR14 / 27x11xR14
Ancla MT (Mud Terrain): front / rear	26x9xR12 / 26x11xR12	26x9xR12 / 26x11xR12	26x9xR12 / 26x11xR12
Terrahawk AT (All Terrain): front / rear	25x9xR12 / 25x11xR12	25x9xR12 / 25x11xR12	25x9xR12 / 25x11xR12
Available Colors			
.....	Green & Yellow, Camouflage, Olive & Black	Green & Yellow, Camouflage, Olive & Black	Green & Yellow, Camouflage, Olive & Black

*Engine horsepower is provided by engine manufacturer for comparison purposes. Actual operating horsepower may be less. ¹Includes 200-lb. (91 kg) operator and 200-lb. (91 kg) passenger and maximum box capacity.